

### HIGH PRESSURE HOSES WITH 90° CONNECTIONS

Part no.	Description	Type	Thread (°BSP)	Max. pressure (bar)	Min. bending radius (mm)	SW (mm)	X (mm)	L (mm)	Weight (kg)
14789589	HOSE ½"-HP-08-00700-00-90	HP-08	½	310	90	27	42	700	0.61
14789570	HOSE ½"-HP-08-01000-00-90	HP-08	½	310	90	27	42	1000	0.76
14789582	HOSE ½"-HP-08-01500-00-90	HP-08	½	310	90	27	42	1500	1.01
14789583	HOSE ½"-HP-08-02000-00-90	HP-08	½	310	90	27	42	2000	1.23
14789535	HOSE ½"-HP-08-02500-00-90	HP-08	½	310	90	27	42	2500	1.6
14789550	HOSE ½"-HP-08-03000-00-90	HP-08	½	310	90	27	42	3000	1.77
14789591	HOSE ½"-HP-08-03500-00-90	HP-08	½	310	90	27	42	3500	2.01
14790117	HOSE ¾"-HP-12-00700-00-90	HP-12	¾	280	150	32	55	700	1.0
14790129	HOSE ¾"-HP-12-01000-00-90	HP-12	¾	280	150	32	55	1000	1.2
14790132	HOSE ¾"-HP-12-01200-00-90	HP-12	¾	280	150	32	55	1200	1.4
14790130	HOSE ¾"-HP-12-01500-00-90	HP-12	¾	280	150	32	55	1500	1.59
14790142	HOSE ¾"-HP-12-02000-00-90	HP-12	¾	280	150	32	55	2000	1.99
14790154	HOSE ¾"-HP-12-02500-00-90	HP-12	¾	280	150	32	55	2500	2.35
14790166	HOSE ¾"-HP-12-03000-00-90	HP-12	¾	280	150	32	55	3000	2.9
14790170	HOSE ¾"-HP-12-03500-00-90	HP-12	¾	280	150	32	55	3500	3.4
14790178	HOSE ¾"-HP-12-04000-00-90	HP-12	¾	280	150	32	55	4000	3.8
14794607	HOSE 1"-HP-16-00700-00-90	HP-16	1	250	160	41	70	700	1.63
14794610	HOSE 1"-HP-16-01000-00-90	HP-16	1	250	160	41	70	1000	2.0
14794612	HOSE 1"-HP-16-01200-00-90	HP-16	1	250	160	41	70	1200	2.38
14794615	HOSE 1"-HP-16-01500-00-90	HP-16	1	250	160	41	70	1500	2.75
14794620	HOSE 1"-HP-16-02000-00-90	HP-16	1	250	160	41	70	2000	3.36
14794625	HOSE 1"-HP-16-02500-00-90	HP-16	1	250	160	41	70	2500	3.98
14794630	HOSE 1"-HP-16-03000-00-90	HP-16	1	250	160	41	70	3000	4.60
14794635	HOSE 1"-HP-16-03500-00-90	HP-16	1	250	160	41	70	3500	5.21
14794640	HOSE 1"-HP-16-04000-00-90	HP-16	1	250	160	41	70	4000	5.83
14794645	HOSE 1"-HP-16-04500-00-90	HP-16	1	250	160	41	70	4500	6.45
14794650	HOSE 1"-HP-16-05000-00-90	HP-16	1	250	160	41	70	5000	7.06

