



3D model is available on request

MP:Mounting plate for valve mounting with 3/4" threaded port

Specifications

Support configuration	Double support				
	14018271	14018273	14018275	14018277	
Part number Aluminium plus	14018271	14018273	14018275	14018277	
Support with rubber,strap with rubber, mounting kit & air breather included	14020166				1H
	14020167				3H
W : Width	380	440	495	580	mm
MW : Mounting Width min / max	195 / 225	200 / 275	220 / 330	250 / 415	mm
Gross volume	155	179	201	236	litres
Working volume	130	150	170	200	litres
Weight tank (Aluminium)	15	16	17	18	kg
A: Suction port	1.5"	1.5"	1.5"	1.5"	BSP
Extra Return Port (RP) size	1"	1"	1"	1"	BSP

The port of the left mounting plate (MP) and the extra return port (RP) are closed with a steel plug and sealing.

Other ports are closed with temporary plastic plugs

Technical notes

- Mount the tank according the mounting instructions - Fill the tank with the recommended hydraulic oil to the centre of the level indicator - Change the oil once a year - Replace the air breather and return filter element twice a year - Do not use the tank to stand on or as a support - Do not weld on the oil tank

Related documentation

Mounting instructions: OIL-0014

Oil specifications: OIL-0011